

Modifications to specifications are possible to do as per request

Engine:

Type Diesel, four stroke, water cooled diesel

Cylinders 4

Power 40 kW at 3000 rpm

Control panel:

Rpm gauge

Hour gauge

Oil pressure warning light

Temperature gauge + warning light

Charger warning light

The engine stops if there is a problem with oil pressure or engine temperature

Hydraulics:

Main pump, 2 pcs load sensing variable displacement pump

8+2 pcs load sensing proportional valves

Components are well known quality products which have been developed specially to be used in water

Synthetic hydraulic oil

2 pcs return oil filters

Chromium plated piston rods of the hydraulic cylinders

Operating pressure max. 260 bar

Control valves / electric couplings 24 V are waterproof EU declaration of conformity for machinery.

Moving on land/or sea:

2 pcs hydraulic driven rubber tracks

speed 0...100 m/min

Standard equipment:

4 pcs working lights

Operators seat, comfortable working position for the operator for marine use

Sun roof

Additional equipment:

Cabin

Echo sounder

A/C

High pressure washer

Toolbox

Winch

Trailer for road transport

Shore conveyor RS 4000

Electric system:

105 Ah/ 24 V accumulator

Water proof bar cables and components of the whole wiring system

Electric switches in the control panel are gold plated to resist corrosion

Coolant and lubrication capacity:

Fuel tank 200 l

Hydraulic oil tank 220 l

Radiator 14 l, 50% antifreeze and lubricant

Operating dimensions:

Portable cutting depth (+) 0,3 m ...(-)1,5 m


Operating width 1,9 m

Transport dimensions:

Adress/Osoite:
Sinkkikuja 4
21600 Parainen
Finland

Tel./Puh:
+358 2 4582 500
Fax:
+358 2 4582 011

Homepage:
www.rsplanering.fi
E-mail:
info@rsplanering.fi



SUUNNITTELU OY
PLANERING AB

RS5000 Specification

Length max. 12,0 m

Hull 6,5 m

Height on road 4,0 m (with cabin)

Height on sea 3,6 m (with cabin)

Weight (AL) 4,0 t

Store conveyor:

Volume 7,5 meter cub.

Loading capacity 1000 kg

Unloading time less than 25 sec.

Unloading height 1,2 ... 2,5 m

Material: PVC cords, safeguards against UV radiation

Construction is based to ship building technology

Manufacturer reserves rights to chance specifications.

Adress/Osoite:
Sinkkikuja 4
21600 Parainen
Finland

Tel./Puh:
+358 2 4582 500
Fax:
+358 2 4582 011

Homepage:
www.rsplanering.fi
E-mail:
info@rsplanering.fi