



SUUNNITTELU OY
PLANERING AB

MOBIWASH INFORMATION

Washing

MobiWash REMOVES EFFECTIVELY slime, weed as well as young BARNACLES. When barnacles grow older, they become more difficult to brush off. To prevent this, one must wash the boat bottom a few times under the season.

Wash operator can generally control the wash and washing by himself. Under windy conditions can e.g. boat owner assist with boat handling.

To wash a boat takes ca. 10-15 minutes. If after normal washing procedure result is not satisfactory, washing can immediately be repeated at a slower pace.

Maximum length of a boat	7.5 meters (24.6 ft)
Max wigth of the boat on water line	2.5m (8.2 ft)
Max weight of boat	1500kg (3306 lb)
Width of opened brushes	3.2m (10.5 ft)
Weight of mobiwash	750kg (1653 lb)
Width of mobiwash	2.3m (7.55 ft)
Lenght of mobiwash	9.5m (31.2 ft)

Hydraulic agregat Brigg&Stratton 16hp with electric start+2 pc hydraulic pumps
Oil capacity ca. 30.0 l

Hydraulic 2 pc hydraulic motors for driving of washingbrushes
2 pc hydraulic cylinders for adjusting of brush/wash angle
Overload valve for wash pressure
Hydraulic winch with stepless speed control
Remote controlled valves

Trailer Hot dip galvanized steel frame
Big keel rolls
Big air filled wheels to support boat on washing
2*750 kg rubber suspension axles
4 pc 185*14 whells
DIN 50 coupling

Adress/Osoite:
Sinkkikuja 4
21600 Parainen
Finland

Tel./Puh:
+358 2 4582 500
Fax:
+358 2 4582 011

Homepage:
www.rsplanering.fi
E-mail:
info@rsplanering.fi

Dry-docking

Boats can be dry-docked when they are not used and thus fouling of the bottom is avoided.

MobiWash is very useful in dry-docking process; when lifted, the boat is simultaneously washed and can be transported to the boatyard and back to water on MobiWash.

Transport

A 4-wheel drive vehicle or tractor is recommended for towing the unit.

MobiWash is 9,5 meters long and weighs 750 kg.

In road transport state width is 2,3 meters, when the brushes are in their uppermost position and locked in a lengthwise direction.

For road transport the unit can be equipped with tail lights (consult local authorities).

Additional equipments:

Magnetic lights for transportation on public roads (Finland)

Warning triangle

Toolbox

Braked axles 2*1500 kg

Technical specifications can be changed without prior notice